



AIRD05 SERIES

Through Hole Radial High Current Power Chokes

FEATURES

- High Saturation Material
- Polyolefin Shrink Tube
- Low DC Resistance
- High Rel, Low Cost


OPTIONS

- Packaging: T&R Standart 1Kpcs
- Tolerance: 10% is standard
- Lower tolerances available.

APPLICATIONS

- Switching Regulator
- RFI Suppression Filters
- SCR & TRIAC Controllers
- Automotive

Part Number	L μH @1KHz	DCR Ohm max.	IDC A max.	Dim (Inches/mm) C Appr.	Dim (Inches/mm) D nom.
AIRD05-1R8M	1.8	0.002	35	1.11/28.194	0.105/2.667
AIRD05-2R2M	2.2	0.002	35	1.11/28.194	0.105/2.667
AIRD05-2R7M	2.7	0.002	35	1.11/28.194	0.105/2.667
AIRD05-3R3M	3.3	0.002	35	1.11/28.194	0.105/2.667
AIRD05-3R9M	3.9	0.003	35	1.11/28.194	0.105/2.667
AIRD05-4R7M	4.7	0.003	35	1.11/28.194	0.105/2.667
AIRD05-5R6M	5.6	0.003	35	1.11/28.194	0.105/2.667
AIRD05-6R8M	6.8	0.003	35	1.11/28.194	0.105/2.667
AIRD05-8R2M	8.2	0.003	35	1.11/28.194	0.105/2.667
AIRD05-100k	10	0.004	35	1.11/28.194	0.105/2.667
AIRD05-120K	12	0.004	35	1.16/29.464	0.105/2.667
AIRD05-150K	15	0.005	35	1.16/29.464	0.105/2.667
AIRD05-180K	18	0.007	27	1.16/29.464	0.094/2.3876
AIRD05-220K	22	0.007	27	1.16/29.464	0.094/2.3876
AIRD05-270K	27	0.008	27	1.16/29.464	0.094/2.3876
AIRD05-330K	33	0.009	27	1.16/29.464	0.094/2.3876
AIRD05-390K	39	0.01	27	1.16/29.464	0.094/2.3876
AIRD05-470K	47	0.011	27	1.16/29.464	0.094/2.3876
AIRD05-560K	56	0.013	21	1.16/29.464	0.094/2.3876
AIRD05-680K	68	0.015	21	1.25/31.750	0.84/2.1336
AIRD05-820K	82	0.017	21	1.28/32.512	0.84/2.1336
AIRD05-101K	100	0.018	21	1.25/31.750	0.84/2.1336
AIRD05-121K	120	0.022	17	1.16/29.464	0.075/1.9152
AIRD05-151K	150	0.025	17	1.16/29.464	0.075/1.9152
AIRD05-181K	180	0.035	13.5	1.10/27.94	0.068/1.7272
AIRD05-221K	220	0.04	13.5	1.10/27.94	0.068/1.7272
AIRD05-271K	270	0.044	13.5	1.10/27.94	0.068/1.7272
AIRD05-331K	330	0.049	13.5	1.11/28.194	0.068/1.7272
AIRD05-390K	390	0.07	11.4	1.15/29.21	0.060/1.524
AIRD05-471K	470	0.078	11.4	1.07/27.178	0.060/1.524
AIRD05-561K	560	0.105	9	1.07/27.178	0.054/1.3716
AIRD05-681K	680	0.115	9	1.07/27.178	0.054/1.3716
AIRD05-820K	820	0.127	9	1.12/28.448	0.054/1.3716
AIRD05-102K	1000	0.176	7.2	1.12/28.448	0.048/1.2192
AIRD05-122K	1200	0.195	7.2	1.12/28.448	0.048/1.2192
AIRD05-152K	1500	0.274	5.5	1.12/28.448	0.043/1.0922
AIRD05-182K	1800	0.302	5.5	1.13/28.702	0.043/1.0922
AIRD05-222K	2200	0.338	5.5	1.16/29.464	0.043/1.0922
AIRD05-272K	2700	0.459	4.5	1.02/25.908	0.039/0.9906
AIRD05-332K	3300	0.642	4	1.02/25.908	0.035/0.8890
AIRD05-392K	3900	0.699	4	1.14/28.956	0.035/0.8890
AIRD05-472K	4700	0.775	4	1.14/28.956	0.035/0.8890
AIRD05-562K	5600	0.843	4	1.14/28.956	0.035/0.8890
AIRD05-682K	6800	1.15	2.8	1.06/26.924	0.031/0.7874
AIRD05-822K	8200	1.26	2.8	1.16/29.464	0.031/0.7874
AIRD05-103K	10000	1.74	2	1.13/28.702	0.028/0.7112
AIRD05-123K	12000	1.92	2	1.13/28.702	0.028/0.7112
AIRD05-153K	15000	2.17	2	1.13/28.702	0.028/0.7112



DIMENSIONS: inches/mm

A	B	P(min)	ØE	ØF
1.60/40.64	1.45/36.83	0.50/12.7	0.10/2.54	0.25/6.35



The AIRD-05.06,07,08 Series of Power Line Choke is available in 367 standard values covering a wide range of inductance and current. The use of high saturation flux density material make these coils ideal for use in switching regulated power supply applications and wherever high current choke values in a small physical size are needed.

- Inductance Testing: HP4284A, HP4285A or equivalent
- RDC: QuadTech 1880 Milliohmeter
- Rated Current: L value drop 10% typ. at I_{DC} against its initial value
- Temperature rise 40°C Max Reference ambient temperature
- Solderability: 75% of the lead wire shall be covered
- Soldering Methods: Wave, Reflow
- Operating Temperature: -25°C to +85°C
- Storage Temperature: -65°C to +125°C
- Terminal bending strength: 24.5N Min
- Moisture resistance: $\Delta L/L \leq \pm 10\%$