



TPE20 SERIES

0.50W EE20-10 - 50/60Hz PCB Mount Transformer

FEATURES

- It is miniaturised to be easily PCB mounted.
- It has very high insulation of 4000Vrms Hi-pot.
- It accords with UL94V-0 flammability requirements.
- Heat-resistance reaches 130°C

OPTIONS

- Packaging unit: 50 pieces
- Bulk packaging is standard
- Custom design available

APPLICATIONS

- Medical equipments
- Industrial equipments
- Industrial controls
- Test equipment
- Industrial computers
- Avionics & telecom

Part Number	Primary (V)	Secondary (V/mA)	No-load (V)	Fig.
TPE201011	230	6 / 83.0	8,9	1
TPE201012	230	9 / 55.0	13,5	1
TPE201013	230	12 / 42.0	19,4	1
TPE201014	230	15 / 34.0	24,6	1
TPE201015	230	18 / 28.0	29,5	1
TPE201018	230	24 / 21.0	39,6	1
TPE201017	230	2x6 / 42.0	2x9.60	2
TPE201018	230	2x9 / 28.0	2x15.20	2
TPE201019	230	2x12 / 21.0	2x19.10	2
TPE201020	230	2x15 / 16.0	2x23.30	2
TPE201021	230	2x18 / 14.0	2x29.20	2
TPE201022	230	2x24 / 10.0	2x38.80	2

Part Number	Primary (V)	Secondary (V/mA)	No-load (V)	Fig.
TPE201023	115	6 / 83.0	8,9	1
TPE201024	115	9 / 55.0	13,5	1
TPE201025	115	12 / 42.0	19,4	1
TPE201026	115	15 / 34.0	24,6	1
TPE201027	115	18 / 28.0	29,5	1
TPE201028	115	24 / 21.0	39,6	1
TPE201029	115	2x6 / 42.0	2x9.60	2
TPE201030	115	2x9 / 28.0	2x15.20	2
TPE201031	115	2x12 / 21.0	2x19.10	2
TPE201032	115	2x15 / 16.0	2x23.30	2
TPE201033	115	2x18 / 14.0	2x29.20	2
TPE201034	115	2x24 / 10.0	2x38.80	2

- Frequency 50/60Hz
- Split-bobbin
- Short-circuit-proof
- Potted under vacuum
- Temperature class to 70°C
- Weight: 0.035kg

