



TPE3018 SERIES

2.3W EI30-18 - 50/60Hz PCB Mount Transformer

FEATURES

- Vacuum filling
- Two compartments bobbins
- Self-extinguishing plastics UL 94 VO
- Degree of protection IP 00
- 80 grams weight

OPTIONS

- Bulk packaging is standard
- Custom design available

APPLICATIONS

- Medical equipments
- Industrial equipments
- Industrial controls
- Test equipment
- Industrial computers
- Avionics & telecom

I PRIMARY VOLTAGE: 230					
Part Number	Secondary V	Secondary mA	No-load V	Amb. Temp. °C	Rating VA
TPE301857	6	383	10,5	T70B	2,3
TPE301858	9	256	15,7	T70B	2,3
TPE301859	12	192	21	T70B	2,3
TPE301860	15	153	25,9	T70B	2,3
TPE301861	18	128	31,4	T70B	2,3
TPE301862	24	96	41,9	T70B	2,3
TPE301863	2 x 6	2 x 192	2 x 10.5	T70B	2,3
TPE301864	2 x 9	2 x 128	2 x 15.7	T70B	2,3
TPE301865	2 x 12	2 x 96	2 x 21	T70B	2,3
TPE301866	2 x 15	2 x 77	2 x 25.9	T70B	2,3
TPE301867*	2 x 18	2 x 64	2 x 31.4	T70B	2,3
TPE301868*	2 x 24	2 x 48	2 x 41.9	T70B	2,3

PRIMARY VOLTAGE: 115					
Part Number	Secondary V	Secondary mA	No-load V	Amb. Temp. °C	Rating VA
TPE301869	6	383	10,5	T70B	2,3
TPE301870	9	256	15,7	T70B	2,3
TPE301871	12	192	21	T70B	2,3
TPE301872	15	153	25,9	T70B	2,3
TPE301873	18	128	31,4	T70B	2,3
TPE301874	24	96	41,9	T70B	2,3
TPE301875	2 x 6	2 x 192	2 x 10.5	T70B	2,3
TPE301876	2 x 9	2 x 128	2 x 15.7	T70B	2,3
TPE301877	2 x 12	2 x 96	2 x 21	T70B	2,3
TPE301878	2 x 15	2 x 77	2 x 25.9	T70B	2,3
TPE301879	2 x 18	2 x 64	2 x 31.4	T70B	2,3
TPE301880	2 x 24	2 x 48	2 x 41.9	T70B	2,3

* To be noted : 2 x 18 V and 2 x 24 non safety transformer approved, conform to EN 61558-2-6 (Isolating transformer).

- Resin class B CEI 85 (20 000 h testing to CEI 126)
- Inherently short-circuits proof transformer
- 30 V model is VDE EN 61558-2-6 certified (production on request)
- Insulation voltage 4 KV
- 100% tested production
- Certification : CCA procedure on request

