



# TPE6623 SERIES

## 30W EI66-23 - 50/60Hz PCB Mount Transformer

### FEATURES

- Vacuum filling
- Two compartments bobbins
- Self-extinguishing plastics UL94V0
- Degree of protection IP 00
- 700 grams weight

### OPTIONS

- Bulk packaging is standard
- Custom design available

### APPLICATIONS

- Medical equipments
- Industrial equipments
- Industrial controls
- Test equipment
- Industrial computers
- Avionics & telecom

PRIMARY VOLTAGE: 230					
Part Number	Secondary V	Secondary mA	No-load V	Amb. Temp. °C	Rating VA
TPE662373	6	5000	6,9	T50B	30
TPE662374	9	333	10,3	T50B	30
TPE662375	12	2500	13,8	T50B	30
TPE662376	15	2000	17,2	T50B	30
TPE662377	18	1667	20,8	T50B	30
TPE662378	24	1250	27,7	T50B	30
TPE662379	2 x 6	2 x 2500	2 x 6.9	T50B	30
TPE662380	2 x 9	2 x 1667	2 x 10.3	T50B	30
TPE662381	2 x 12	2 x 1250	2 x 13.8	T50B	30
TPE662382	2 x 15	2 x 1000	2 x 17.2	T50B	30
TPE662383	2 x 18	2 x 833	2 x 20.8	T50B	30
TPE662384*	2 x 24	2 x 625	2 x 27.7	T50B	30

PRIMARY VOLTAGE: 115					
Part Number	Secondary V	Secondary mA	No-load V	Amb. Temp. °C	Rating VA
TPE662385	6	5000	6,9	T50B	30
TPE662386	9	333	10,3	T50B	30
TPE662387	12	2500	13,8	T50B	30
TPE662388	15	2000	17,2	T50B	30
TPE662389	18	1667	20,8	T50B	30
TPE662390	24	1250	27,7	T50B	30
TPE662391	2 x 6	2 x 2500	2 x 6.9	T50B	30
TPE662392	2 x 9	2 x 1667	2 x 10.3	T50B	30
TPE662393	2 x 12	2 x 1250	2 x 13.8	T50B	30
TPE662394	2 x 15	2 x 1000	2 x 17.2	T50B	30
TPE662395	2 x 18	2 x 833	2 x 20.8	T50B	30
TPE662396	2 x 24	2 x 625	2 x 27.7	T50B	30

\* To be noted : 2 x 24 V non safety transformer approved, conform to EN 61558-2-6 (isolating transformer).

- Resin class B CEI 85 (20 000 h testing to CEI 126)
- Fuse protection on secondary side (see diagram) to be assumed by customer
- 30 V and 36 V models are VDE EN 61558-2-6 certified (production on request)

- Insulation voltage 4 kV
- 100% tested production
- Certification : CCA procedure on request

